



Series EWS 2.0" L Duplex Commercial Activated Carbon Backwashable Filter

STANDARD FEATURES

- ◆ 2" NPT inlet and outlet top mounted lead free brass epoxy coated control valve.
- ◆ Electronic flow meter with accuracy within plus or minus 5 percent, flow rate range 1.5 to 75 gpm. Gallons range 500 to 250,000, totalizer 1 to 9,999,000 gallons.
- ◆ Service flow rate up to 75 gpm, peak flow rate up to 88 gpm, backwash flow rates up to 50 gpm.
- ◆ Fully adjustable 6 cycle controls backwash, slow/fast rinse and service. 2 additional cycles for backwash and rinse
- ◆ Cycles of operation. Cycle One backwash 1-20 minutes or off, Cycle Two slow rinse 1-99 minutes or off, Cycle Three second backwash 1-20 minutes or off, Cycle Four fast rinse 1-20 minutes or off, Cycle Five service.
- ◆ Four methods to initiate regeneration, meter immediate, meter delayed, time clock delayed or pressure differential.
- ◆ 1 1/2" water distribution system utilizing single point distributor or hub and laterals for maximum flowrates.
- ◆ Operating pressure 20-125 psi / 138-861 kpa, operating temperature 40°F - 110°F (5°C - 44°C).
- ◆ Solid state microprocessor c/w display for time of day, days until next regeneration, volume remaining, current flow rate and total volume used (totalizer).
- ◆ Double backwash for optimum regeneration cleaning ability.
- ◆ Duplex alternating motorized electronic control valve (2").
- ◆ 12 volt output AC transformer. 12 or 24 hour time clock.
- ◆ 1 - 28 days override on control valve programming.
- ◆ 1 1/4" FPT drain line.

Excalibur Water EWS 2.0" L Duplex Commercial Activated Carbon Backwashable Filter - SPECIFICATIONS

Model	Filter Tank Dia. X Ht.	Pipe Size Inlet/Outlet	Approx. Space Required Ins - (mm)				Shipping Weight	Shipping Weight
	Inches (mm)	Inches (mm)	Height	Depth	Width Single Duplex		Single Lbs (Kg.)	Duplex Lbs (Kg.)
EWS FD2LC4	16 x 65 (406 x 1651)	2 x 2 (50 x 50)	73 (1854)	22 (558)	28 (711)	56 (1422)	425 (193)	850 (386)
EWS FD2LC5	21 x 62 (533 x 1574)	2 x 2 (50 x 50)	70 (1778)	27 (685)	33 (838)	66 (1676)	525 (238)	1050 (386)
EWS FD2LC6	21 x 62 (533 x 1574)	2 x 2 (50 x 50)	70 (1778)	27 (685)	33 (838)	66 (1676)	550 (258)	1100 (500)
EWS FD2LC7	21 x 62 (533 x 1574)	2 x 2 (50 x 50)	70 (1778)	27 (685)	33 (838)	66 (1676)	575 (261)	1150 (522)
EWS FD2LC8	24 x 72 (609 x 1828)	2 x 2 (50 x 50)	80 (2032)	30 (762)	36 (914)	72 (1828)	650 (295)	1300 (590)

Model	Media Volume Per Vessel Cubic Ft (Cubic Meters)	Total Media Capacity Cubic Ft (Cubic Meters)	Dechlorination Per Vessel		Organics Absorption Per Vessel		BKW GPM (LPS)
			Continuous Flow Rate 15 Psi Pressure Drop (LPS)	Peak Flow Rate (LPS)	Continuous Flow Rate 15 Psi Pressure Drop (LPS)	Peak Flow Rate (LPS)	
EWS FD2LC4	4 (.112)	8 (.224)	12 (.75)	18 (1.13)	8 (.50)	12 (.75)	50 (2.27)
EWS FD2LC5	5 (.14)	10 (.28)	15 (.94)	22 (1.38)	10 (.63)	15 (.94)	50 (2.27)
EWS FD2LC6	6 (.168)	12 (.336)	18 (1.13)	27 (1.70)	12 (.75)	18 (1.18)	50 (2.27)
EWS FD2LC7	7 (.196)	14 (.392)	21 (1.32)	32 (2.02)	16 (1.00)	24 (1.51)	50 (2.27)
EWS FD2LC8	8 (.224)	16 (.448)	24 (1.51)	36 (2.27)	20 (1.26)	30 (1.89)	50 (2.27)

EWS GRANULAR ACTIVATED CARBON IS DESIGNED FOR REDUCTION OF TASTE, ODOURS, AND DISSOLVED ORGANIC CHEMICALS. EWS ACTIVATED CARBON IS MANUFACTURED FROM SELECT GRADES OF BITUMINOUS COAL TO PRODUCE A HIGH DENSITY, DURABLE GRANULAR PRODUCT CAPABLE OF WITHSTANDING THE ABRASION AND DYNAMICS ASSOCIATED WITH REPEATED HYDRAULIC TRANSPORT, BACKWASHING AND MECHANICAL HANDLING. ACTIVATION IS CAREFULLY CONTROLLED TO PRODUCE EXCEPTIONALLY HIGH INTERNAL SURFACE AREA WITH OPTIMUM PORE SIZE FOR THE ADSORPTION OF A BROAD RANGE OF HIGH AND LOW MOLECULAR WEIGHT ORGANIC CONTAMINANT'S. TO OBTAIN MAXIMUM EFFICIENCY OF THE ACTIVATED CARBON IN THE ADSORPTION PROCESS, IT IS DESIRABLE TO HAVE THE GREATEST POSSIBLE SURFACE AREA IN THE SMALLEST PRACTICAL VOLUME. THIS IS NECESSARY BECAUSE THE RATE OF ADSORPTION IS PROPORTIONAL TO THE AMOUNT OF SURFACE AREA OF THE ADSORBING MEDIUM MEDIA. EWS HAS A SURFACE AREA OF 850 SQUARE METERS PER GRAM. THIS RESULTS IN HIGH EFFICIENCY AND GREATER SYSTEM ECONOMY. EWS ACTIVATED CARBON REQUIRES PERIODIC BACKWASHING TO ELIMINATE ACCUMULATED SUSPENDED MATTER AND TO RE- GRADE THE FILTER BED. EWS ACTIVATED CARBON HAS AN EXTREMELY HIGH CAPACITY BUT MUST BE REPLACED WHEN THE FILTER BED LOSES THE CAPACITY FOR REDUCTION OF TASTE, ODOUR AND ORGANICS.

Canada

• 220 Bayview Drive Unit 18, Barrie Ontario L4N 4Y8 •